



SEESHEEN
see the endo-sheen

UR Series




**Flexible video
Ureterorenoscope**



CE 0197

UR series

Flexible video ureterorenoscope specification

Safety	Standard	CE marking according to MDD93/42/EEC directive Grade: IIa; IEC60601-1,IEC60601-2-18,IEC60601-1-2approved.	
	Operating condition	Temperature: 15°C-37 °C, atmospheric pressure: 700-1060hPa, Humidity: 30%-85%.	
	Storage condition	Temperature: -47°C-70 °C, atmospheric pressure: 700-1060hPa, Humidity: 10%-95%.	
Operational Part	Model	UR-1331	UR-1328
	Type	Flexible	Flexible
	Image Sensor	CMOS (Complementary Metal Oxide Semiconductor),Chip-on-tip	
	System resolution	9 line pairs/mm	
	View Angle	120°	120°
	Direction of view	0°	0°
	View Depth	3-50mm	3-50mm
	Insertion Tube OD	∅ 3.1mm	∅ 2.8mm
	Channle ID	∅ 1.2mm	∅ 1.2mm
	Bending(up/down)	U275°/D275°	U275°/D275°
	Working Length	670mm	670mm
	Full length	2950 mm with video cable; 940mm exclude video cable	2950 mm with video cable; 940mm exclude video cable
	Weight	≤ 450g	≤ 450g
	Insertion Rotation	L120°/R120°	L120°/R120°
	Enlarged view of tip	<ol style="list-style-type: none"> 1. Object lens 2. LED light source 3. Forceps pipe outlet 	<ol style="list-style-type: none"> 1. Object lens 2. LED light source 3. Forceps pipe outlet 
	Compatible image processor		
	Control Button	Three Buttons(Photograph recording, freeze, image sizes)	
	Water Proof Grade	Equals to IPX7 and complied to BS ISO 8600-7-2012	